

qty	thread	length	vented/unvented	assembly	nut or bolt	
8	8-32	0.750	unvented	top heater	bolt	
2	1/4-20		spring top plate	spring top plate	nut	
2	1/4-20	0.750	spring top plate	spring top plate	bolt	
4	8-32		unvented	spring top plate	nut	
2	8-32	0.750	unvented	spring top plate	bolt	
1	8-32	1.000	vented	lifting subassembly	bolt	
1	8-32		unvented	lifting subassembly	thin nut	
6	8-32	6.000	unvented	lifting subassembly	bolt	
8	6-32	0.375	unvented	heater holder assembly	bolt	
2	1/4-20	1.500	unvented	Extraneous Support	bolt	
2	1/4-20		unvented	Extraneous Support	nut	
8	8-32	1.000	unvented	Extraneous Support	bolt	
4	1/4-20	0.500	unvented	nuBottomCart	bolt	
2	8-32	0.500	unvented	nuBottomCart	bolt	
1	8-32	1.500	unvented	assembled v2 cord cap	bolt	
1	8-32		unvented	assembled v2 cord cap	nut	
2	8-32	0.500	vented	assembled v2 cord cap	bolt	
12			unvented	throughout	conical spring washers	
4	8-32	0.250	vented	rail mount for pulleys	bolt	needs to be flat head
3	8-32	2.000	unvented	spool redux	bolt	
7	8-32		unvented	spool redux	nut	
1	8-32	0.750	unvented	spool redux	bolt	
2	8-32	0.500	unvented	spool redux	bolt	
8	8-32	0.500	unvented	top heater	helicoil inserts	
					retaining bolt for rod mount base	